



# S4SSE TRIM BOARDS PROTECTED OF \$\times \text{TRADITIONAL}

(for interior & exterior use only) available with a 30yr warranty

## SMOOTH SURFACE 4 SIDES

All WindsorONE Trim Boards come with a three coat, 100% acrylic latex, industry leading primer ensuring a smooth finish. Bottom line, it saves you time and money on the jobsite.

#### AVAILABLE SIZES:

### TRADITIONAL or PROTECTED

IKADIIIUNAL	O PROTECTED
16' +Protected ජ Traditional in	30 Year warranty*
	on +1rotectea hoards
16' lengths**	
1x2 □	1x2 <b>—</b>
1x3 □	1x3
1x4 <u></u> □	1x4 <b>—</b>
1x5 □	1x5
1x6 □ □	1x6
1x8 =====	1x8
1x10 ======	1x10
1x12	1x12
<sup>5</sup> / <sub>4</sub> x 3 □	$^{5}/_{4}$ x 3
<sup>5</sup> / <sub>4</sub> x 4 □□	<sup>5</sup> / <sub>4</sub> x 4
<sup>5</sup> / <sub>4</sub> x 5 □□□	<sup>5</sup> / <sub>4</sub> x 5
<sup>5</sup> / <sub>4</sub> x 6 □□□	$^{5}/_{4} \times 6$
<sup>5</sup> / <sub>4</sub> x 8 □□□	$^{5}/_{4}$ x 8
<sup>5</sup> / <sub>4</sub> x 10	$\frac{5}{4} \times 10$
<sup>5</sup> / <sub>4</sub> x 12	<sup>5</sup> / <sub>4</sub> x 12

\*inquire about 12' & 20' lengths in your area

#### INSTALLATION SIMPLIFIED\*:



Prime ALL cuts (even butt joints and miters, unless using exterior grade glue).





Do not install trim boards that have a moisture content over 18%. (For interior use, boards must be acclimated).



Maintain clearances of 6" 2" & 1/4."

# \*SEE FULL INSTALLATION INSTRUCTIONS.

WindsorONE+ should be stored, installed, handled & maintained correctly for the best performance. For complete installation guidelines & the WindsorONE+ protected warranty, visit-WindsorONE.com or call 888.229.7900.



